


60 TRAY / 9.6 M² COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



30-90°
Precision
Thermostats



Glass
Observation
Window



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

60CUD SPECIFICATIONS

Max Power Usage	5.75 kW (1.9 kW x 3 Zones)	Total Tray Area	9.6 m ²
Avg Power Usage	2.3 kW (766.66667 W x 3 Zones)	Total Trays	60
Voltage / Frequency	200-240V/50-60Hz	Tray Dimensions	40 x 40 cm
Max Amperage	23A	Space Between Trays	35 mm
Safety Breaker Required	Single Phase/25A	Tray Mesh Spacing	8 x 8 mm
Temperature Range	Ambient Mode, 30 - 90°C	Machine Weight	86.2 kg
Timer	0 - 99hr	Product Dimensions (W x H x D)	1410 x 930 x 555 mm
Independent Zones	3	Features	Memory Function, Ambient Air Mode
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminium door handle; Tempered glass observation window; Control Panel with PVC finish.		