





SERVING THE FOOD INDUSTRY SINCE 1951

Insulated Beverage Server

Item: 80901 | 80902 | 80903

9.4L 18L 44.5L



FEATURES

- Seamless double-wall PE construction and foamed-in-place polyurethane insulation ensures years of reliable service and prevents liquids from seeping walls.
- · Molded-in mounting plates prevent latches from pulling out.
- Drip-proof recessed spigot allows for easy accessing and can be easily adjusted without tools.
- Wide service opening accommodates larger cup or coffee pots when units are stacked on a riser.
- · Each unit includes a set of beverage label.
- Interlocking construction allows for stable stacking and space saving.

Telephone: 1-800-465-0234

Fax: (905) 607-0234

Email: sales@omcan.com

Website: www.omcan.com









Insulated Beverage Server

ITEM: 80901 | 80902 | 80903







Recessed faucet

- · Accommodates for larger cups.
- Two positions, one for continuous pouring.
- · And the other for individual dispensing.



Insulation effect

Initia Hot	l Temperature	1H	2H	3Н	4H
	80. C	78 ⁻ C	76 [.] C	74° C	73 [.] C
	I Temperature	1H	2H	зн	4H
Cold	0. C	1.5° C	2 ⁻ C	3. C	4. C

TECHNICAL SPECIFICATIONS							
Item	80901	80902	80903				
Capacity	9.4 L/ 2.5 gal.	18 L/ 5 gal.	44.5 L/ 11.8 gal.				
Material	PE, PU						
Color	Brow						
Net Dimensions (WDH)	16.5" x 9.1" x 18.5" 420 x 230 x 470 mm	16.5" x 9.1" x 24" 420 x 230 x 620 mm	21" x 16.3" x 24.8" 530 x 415 x 630 mm				
Gross Dimensions (WDH)	17" x 9.4" x 19" 430 × 240 × 480	17" x 9.4" x 24.8" 430 × 240 × 630	21.3" x 16.7" x 25.6" 540 ×425 × 650				
Net Weight	11.7 lb./ 5.3 kg	17.4 lb./ 7.9 kg	28.9 lb./ 13.1 kg				
Gross Weight	13.7 lb./ 6.2 kg	19.6 lb./ 8.9 kg	33.1 lb./ 15 kg				

