




28 TRAY / 11.9 M² COMMERCIAL-GRADE DEHYDRATOR

COMMERCIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL



Uniform Drying
Without
Rotation



Completion
Cooling Cycle



Time and
Temp Memory
Function



99 Hour
Timer



30-90°
Precision
Thermostats



Glass
Observation
Window



Ambient
Air Mode



Food-Grade
304 Stainless
Steel

28CUD SPECIFICATIONS

Max Power Usage	7 kW (3.5 kw x 2 Zones)	Total Tray Area	11.9 m ²
Avg Power Usage	2.8 kW (1.4 kW x 2 Zones)	Total Trays	28
Voltage / Frequency	200-240V/50-60Hz	Tray Dimensions	50 x 85 cm
Max Amperage	29A	Space Between Trays	50 mm
Safety Breaker Required	Single Phase/32A	Tray Mesh Spacing	12 x 12 mm
Temperature Range	Ambient Mode, 30 - 90°C	Machine Weight	140kg
Timer	0 - 99hr	Product Dimensions (W x H x D)	880 x 1690 x 670 mm
Independent Zones	2	Features	Memory Function, Ambient Air Mode
Product Material	Food grade 304 stainless steel trays; Commercial grade stainless steel housing & latches; Aluminum door handle; Tempered glass observation window; Control Panel with PVC finish.		